



BC BUILDING PRODUCTS
THE ENVELOPE SPECIALISTS

SAFETY DATA SHEET

Basalite Fast Patch

Manufacturer: Basalite / SAKRETE

The following pages are the manufacturer's original document, reproduced unaltered (SDS Version 1.0, revision date 01/29/2021).

Always refer to the manufacturer's most current SDS.

SUPPLIED BY BC BUILDING PRODUCTS

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture

Product name : CONTECH Structural Patch;
Fast Patch (Summer);
Fast Patch (Winter);
Trafic Patch (Fine);
Trafic Patch (Coarse);
Aqua Tite/Plug Tite;
Damp Seal;
MS10000 (Permacast);
PL8000 (Permacast);
TOP N BOND;
Flo Coat (SAKRETE)

1.2. Recommended use and restrictions on use

Recommended use : Building and construction work

1.3. Supplier

Manufacturer

Basalite Concrete Products, ULC
Basalite Surrey
13066-88th Avenue
Surrey, BC V3W 3K3

Distributor

Basalite Concrete Products, ULC
Basalite Surrey
13066-88th Avenue
Surrey, BC V3W 3K3

1.4. Emergency telephone number

Emergency number : CHEMTREC 1 (800) 424-9300

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Skin Irrit. 2 H315
Eye Dam. 1 H318
Skin Sens. 1 H317
Carc. 1A H350
STOT SE 3 H335
STOT RE 1 H372

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) :

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H350 - May cause cancer
H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

Precautionary statements (GHS-CA) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear eye protection, face protection, protective clothing, protective gloves
P308+P313 - IF exposed or concerned: Get medical advice/attention

Basalite Patch Products

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P302+P352 - IF ON SKIN: Wash with plenty of water
P362+P364 - Take off contaminated clothing and wash it before reuse
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P312 - Call a POISON CENTER or doctor if you feel unwell
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Traffic Patch (Fine) / Traffic Patch (Coarse):

Name	Product identifier	%
Quartz	(CAS-No.) 14808-60-7	60 - 65
Calcium Sulfoaluminate Cement	(CAS-No.) 960375-09-1	21.85 – 22.86

All other products:

Name	Product identifier	%
Quartz	(CAS-No.) 14808-60-7	< 65
Cement, portland, chemicals	(CAS-No.) 65997-15-1	21.85 - 99.5
Calcium oxide	(CAS-No.) 1305-78-8	21.85 - 99.5
Calcium Sulfoaluminate Cement	(CAS-No.) 960375-09-1	13 ¹
Calcium hydroxide	(CAS-No.) 1305-62-0	1.33 – 3.52 ²
Chromium, ion (Cr 6+)	(CAS-No.) 18540-29-9	< 0.1

¹Only present in Flo Coat (SAKRETE)

²Only present in CONTECH Structural Patch, Fast Patch (Summer/Winter), and Aqua Tite/Plug Tite

Comments : The concentrations listed represent actual ranges that result from batch variability.

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause burns in the presence of moisture. Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Basalite Patch Products

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.3. Specific hazards arising from the hazardous product

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Silicon oxides.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2. Methods and materials for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Vacuum or sweep material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Do not breathe dust, fume, gas, mist, spray, vapours. Avoid generating dust. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a dry, cool and well-ventilated place. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Cement, portland, chemicals (65997-15-1)		
USA - ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
Calcium oxide (1305-78-8)		
USA - ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
Quartz (14808-60-7)		
USA - ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate matter)
Calcium hydroxide (1305-62-0)		
USA - ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Basalite Patch Products

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Hand protection:

Wear suitable waterproof gloves

Eye protection:

Wear eye/face protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: No data available
Colour	: Various
Odour	: Odourless
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not flammable
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative density	: No data available
Solubility	: Insoluble
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Incompatible materials. Moisture.
Incompatible materials	: Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Silicon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Basalite Patch Products

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Calcium hydroxide (1305-62-0)	
LD50 oral rat	7340 mg/kg
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: May cause cancer.
Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs (lungs) through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause burns in the presence of moisture. Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Calcium oxide (1305-78-8)	
LC50 fish 1	1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])
Chromium, ion (Cr 6+) (18540-29-9)	
LC50 fish 1	36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 fish 2	7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

12.2. Persistence and degradability

Basalite Patch Products	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Basalite Patch Products	
Bioaccumulative potential	Not established.
Calcium oxide (1305-78-8)	
BCF fish 1	(no bioaccumulation)
Calcium hydroxide (1305-62-0)	
BCF fish 1	(no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

Basalite Patch Products

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

No additional information available

14.3. Air and sea transport

No additional information available

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories except for:

Calcium Sulfoaluminate Cement	CAS-No. 960375-09-1
Wollastonite (Ca(SiO ₃))	CAS-No. 13983-17-0

15.2. International regulations

No additional information available

SECTION 16: Other information

Date of issue : 06/21/2017
Revision date : 01/29/2021
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.