



BC BUILDING PRODUCTS
THE ENVELOPE SPECIALISTS

TECHNICAL DATA SHEET

DELTA® MULTI-BAND Tape for WRBs

Manufacturer: Dörken Systems Inc.

The following pages are the manufacturer's original document,
reproduced unaltered (revision not shown on document).

SUPPLIED BY BC BUILDING PRODUCTS

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca

TECHNICAL DATA SHEET

DELTA®-MULTI BAND

Premium Self-adhering Tape

MATERIAL

DELTA®-MULTI BAND is a premium durable tape that is an important component of complete DELTA® air and moisture control systems. DELTA®-MULTI BAND is made of a special reinforced UV-stabilized polyethylene (PE) film and highly aggressive solvent-free acrylic adhesive with an easily removed paper release liner. It is fully compliant with

AAMA 711-13 Voluntary Specification for Self Adhering Flashing Used for Installation of Exterior Wall Fenestration Products. Specially designed for use with all DELTA® air and water-resistive barrier membranes, DELTA®-MULTI BAND ensures optimal energy-efficient performance.

PROPERTIES

DELTA®-MULTI BAND helps make an enclosure system air and water-tight. It adheres tenaciously to common building substrates and to all DELTA® membranes, making it an ideal component in an air and water tight wall, roof and foundation assembly. In addition, DELTA®-MULTI BAND is universal adhesive tape with very strong adhesion and is highly resistant to aging. Suitable for interior and exterior use, DELTA®-MULTI BAND is non-bituminous, solvent free, low odor, and suitable for LEED® rated projects by contributing to a more durable, sustainable and energy-efficient structure.

APPLICATION

DELTA®-MULTI BAND is used to seal the interfaces between rough openings, for windows and doors. DELTA®-MULTI BAND contributes to the air and water tightness of the building enclosure by sealing overlaps (end laps and side laps) of DELTA® air and water-resistive barriers.



DELTA® products support sustainable and energy-efficient building practices, including efforts toward achieving LEED® certification (LEED® for New Construction & Major Renovations, LEED® for Core and Shell, LEED® for Existing Buildings and LEED® for Homes).

For technical support, call our technical support team at 1-888-4DELTA4 (1-888-433-5824) extension 326, or visit www.dorken.com.

Technical Data

Product name	DELTA®-MULTI BAND	
Color	White with red print	
Tensile strength	2.67 N/mm (Breaking force) - PASS	AAMA 711-13 § 5.1 ASTM D5035-11 (2015) Requirement: (0.5 N/mm)
Elongation at break	22.3%	AAMA 711-13 § 5.1 ASTM D5035-11 (2015)
Water penetration resistance around nails	Pass (Initial observation)	AAMA 711-13 § 5.2 ASTM D1970-13 § 7.9 Mod.
	Pass (After thermal cycling)	
90° peel adhesion	0.58 N/mm (over OSB) - PASS	AAMA 711-13 § 5.3 Requirement: (0.26 N/mm)
	1.55 N/mm (over Aluminum) - PASS	
	0.89 N/mm (over Vinyl) - PASS	
	0.73 N/mm (over Plywood) - PASS	
	0.47 N/mm (over DELTA®-VENT SA) - PASS	
Accelerated aging	2.04 N/mm (Peel adhesion) - PASS	AAMA 711-13 § 5.4 Requirement: (0.26 N/mm)
Elevated temperature exposure	1.88 N/mm (Peel adhesion) - PASS	AAMA 711-13 § 5.5 Requirement: (0.26 N/mm)
Thermal cycling	2.18 N/mm (Peel adhesion) - PASS	AAMA 711-13 § 5.6 Requirement: (0.26 N/mm)
Self-adhering polymer low temperature flexibility	Pass - MD No visible sign of cracking	ASTM D1970-13 Section 7.6 Requirement: (Must pass -18°C)
	Pass - MD Head of water test	
Adhesion of self adhering flashing after water immersion	1.76 N/mm (Peel adhesion initial) - PASS	AAMA 711-13 § 5.8 Requirement: (0.26 N/mm)
	1.40 N/mm (Peel adhesion after water immersion) - PASS	
Resistance of self adhering flashing to peeling from itself	No - Peeling - PASS	AAMA 711-07 § 5.9 Requirement: Maximum edge curl: 13mm Maximum corner curl: 75 mm
	No - Buckling - PASS	
	No - Rippling - PASS	
	0 mm - Maximum edge curl - PASS	
	0 mm - Maximum corner curl - PASS	
Roll Size	2 1/2" x 82' (6 cm x 25 m) 10 rolls per box	
	4" x 82' (10 cm x 25 m) 6 rolls per box	