



BC BUILDING PRODUCTS
THE ENVELOPE SPECIALISTS

TECHNICAL DATA SHEET

Resisto Redzone Stick VP

Manufacturer: Resisto (Soprema Inc.)

The following pages are the manufacturer's original document,
reproduced unaltered (revision not shown on document).

SUPPLIED BY BC BUILDING PRODUCTS

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca



RESISTO VP SA

VAPOR PERMEABLE AIR BARRIER MEMBRANE

RESISTO VP SA is a self-adhesive vapor-permeable air-barrier membrane with a trilaminated polypropylene complex on its surface. Used in walls, its superior breaking and tear strength, combined with a self-adhesive underface, protected by a silicone release film, make it very easy to install. It can be used on most building surfaces such as masonry, concrete, wood, and gypsum.

RESISTO®

BUILDING PRODUCTS

Roofing Waterproofing Wall Systems Insulation

BENEFITS

- Superior breaking and tear strength
- Easy to install - no wrinkles/bubbles
- No primer needed
- Adhesion to most construction materials
- UV exposure up to 180 days
- Self-sealing membrane ensuring continuous waterproofing
- Allows humidity to exit the wall assembly, preventing moisture build-up



RESISTO VP SA

THICKNESS	–	24 mils (0.6 mm)
DIMENSION	–	47 in × 98 ft (1.2 m × 30 m)
SURFACE	–	Trilaminated polypropylene complex
UNDERFACE	–	Self-adhesive, covered with a silicone release film
WATER VAPOR PERMEANCE	ASTM E96	Method A: 10 perms (572 ng/Pa•s•m ²) Method B: 13 perms (744 ng/Pa•s•m ²)
MINIMUM APPLICATION TEMPERATURE	–	40°F
TENSILE STRENGTH, MD/XD	ASTM D882	6.4 kN/m / 4.4 kN/m
BREAKING STRENGTH, MD/XD	ASTM D5034	723 N / 484 N
AIR PERMEANCE AT 75 PA	ASTM E2178	0.0025 L/s•m ²
AIR LEAKAGE RESISTANCE AT 75 PA	ASTM E2357	Pass
NAIL SEALABILITY	ASTM D1970 modified	Pass
FLAME SPREAD AND SMOKE DEVELOPMENT	ASTM E84	Class A
ASSEMBLY FIRE RESISTANCE (UNDER POLYISO INSULATION ONLY)	Component of an NFPA 285 assembly	Pass

*For applications below 40 °F (4 °C), please contact your RESISTO sales representative for other alternatives. Meets all ICC-ES AC-308 standard requirements.

COMPLEMENTARY PRODUCTS

REDZONE



ALL-WEATHER BUTYL FLASHING TAPE



REDZONE CORNER GUARD



RESISTO VP SA	24795	383 ft ² (36m ²)	25 rolls/pallet
---------------	-------	---	-----------------