



**BC BUILDING PRODUCTS**  
THE ENVELOPE SPECIALISTS

---

**SAFETY DATA SHEET**

# **Sikaflex -1a**

Manufacturer: Sika Canada Inc.

The following pages are the manufacturer's original document,  
reproduced unaltered (revision date 03/07/2025).

**Always refer to the manufacturer's most current SDS.**

**SUPPLIED BY BC BUILDING PRODUCTS**

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

### SECTION 1. IDENTIFICATION

Product name : Sikaflex®-1A

Other means of identification : No data available

Company name : www.sika.ca  
Canada  
Pointe-Claire, QC H9R 4A9  
601, avenue Delmar  
Sika Canada Inc.

Telephone : (514) 697-2610 / 1 (800) 933-7452

Telefax : (514) 694-2792

E-mail address : ehs@ca.sika.com

Emergency telephone : CANUTEC (collect) (613) 996-6666 (24 hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 2

#### GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.  
H334 May cause allergy or asthma symptoms or breathing diffi-



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

culties if inhaled.  
H350 May cause cancer by inhalation.  
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements : P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P260 Do not breathe mist or vapors.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.  
P284 In case of inadequate ventilation wear respiratory protection.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

None known.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

### Components

| Chemical name                       | CAS-No.    | Classification                                                                                                                                                          | Concentration<br>(% w/w) |
|-------------------------------------|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| xylene                              | 1330-20-7  | Flam. Liq. 3; H226<br>Acute Tox. 4; H332<br>Acute Tox. 4; H312<br>Skin Irrit. 2; H315<br>Eye Irrit. 2A; H319<br>STOT SE 3; H335<br>STOT RE 2; H373<br>Asp. Tox. 1; H304 | >= 1 - < 5               |
| ethylbenzene                        | 100-41-4   | Flam. Liq. 2; H225<br>Acute Tox. 4; H332<br>STOT RE 2; H373<br>Asp. Tox. 1; H304<br>Carc. 2; H351<br>Eye Irrit. 2A; H319                                                | >= 0.1 - < 1             |
| 4,4'-methylenediphenyl diisocyanate | 101-68-8   | Acute Tox. 4; H332<br>Skin Irrit. 2; H315<br>Eye Irrit. 2B; H320<br>Resp. Sens. 1; H334<br>Skin Sens. 1; H317<br>STOT SE 3; H335<br>STOT RE 2; H373                     | >= 0.1 - < 1             |
| Quartz (SiO <sub>2</sub> ) >5µm     | 14808-60-7 | Carc. 1A; H350<br>STOT RE 1; H372<br>STOT SE 3; H335                                                                                                                    | >= 0.1 - < 1             |
| aromatic polyisocyanate             | 53317-61-6 | Eye Irrit. 2A; H319<br>Skin Sens. 1; H317                                                                                                                               | >= 0.1 - < 1             |

Actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

- |                                                             |   |                                                                                                                                                                                                                                                                                                             |
|-------------------------------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| If swallowed                                                | : | Clean mouth with water and drink afterwards plenty of water.<br>Do not induce vomiting without medical advice.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>Obtain medical attention.                                                           |
| Most important symptoms and effects, both acute and delayed | : | Asthmatic appearance<br>Allergic reactions<br>sensitizing effects<br>May cause an allergic skin reaction.<br>May cause allergy or asthma symptoms or breathing difficulties if inhaled.<br>May cause cancer by inhalation.<br>May cause damage to organs through prolonged or repeated exposure if inhaled. |
| Notes to physician                                          | : | Treat symptomatically.                                                                                                                                                                                                                                                                                      |

---

### SECTION 5. FIRE-FIGHTING MEASURES

- |                                                |   |                                                                                                                                                                                                                         |
|------------------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Suitable extinguishing media                   | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.                                                                                                                 |
| Further information                            | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.                                                                                                                                                          |

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |                                                                     |   |                                                                                                                                                             |
|---------------------------------------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Deny access to unprotected persons.                                                                                   |
| Environmental precautions                                           | : | Do not flush into surface water or sanitary sewer system.<br>Local authorities should be advised if significant spillages cannot be contained.              |
| Methods and materials for containment and cleaning up               | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).<br>Keep in suitable, closed containers for disposal. |

---

### SECTION 7. HANDLING AND STORAGE

- |                              |   |                                                 |
|------------------------------|---|-------------------------------------------------|
| Advice on protection against | : | Normal measures for preventive fire protection. |
|------------------------------|---|-------------------------------------------------|



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

fire and explosion

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

| Components                          | CAS-No.   | Value type<br>(Form of exposure) | Control parameters / Permissible concentration | Basis     |
|-------------------------------------|-----------|----------------------------------|------------------------------------------------|-----------|
| xylene                              | 1330-20-7 | TWA                              | 100 ppm<br>434 mg/m3                           | CA AB OEL |
|                                     |           | STEL                             | 150 ppm<br>651 mg/m3                           | CA AB OEL |
|                                     |           | TWAEV                            | 100 ppm<br>434 mg/m3                           | CA QC OEL |
|                                     |           | STEV                             | 150 ppm<br>651 mg/m3                           | CA QC OEL |
|                                     |           | TWA                              | 100 ppm                                        | CA BC OEL |
|                                     |           | STEL                             | 150 ppm                                        | CA BC OEL |
|                                     |           | TWA                              | 20 ppm                                         | ACGIH     |
| ethylbenzene                        | 100-41-4  | TWA                              | 100 ppm<br>434 mg/m3                           | CA AB OEL |
|                                     |           | STEL                             | 125 ppm<br>543 mg/m3                           | CA AB OEL |
|                                     |           | TWA                              | 20 ppm                                         | CA BC OEL |
|                                     |           | TWAEV                            | 20 ppm                                         | CA QC OEL |
|                                     |           | TWA                              | 20 ppm                                         | ACGIH     |
| 4,4'-methylenediphenyl diisocyanate | 101-68-8  | TWA                              | 0.005 ppm                                      | CA BC OEL |
|                                     |           | C                                | 0.01 ppm                                       | CA BC OEL |



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

|                                 |            |                                     |                          |           |
|---------------------------------|------------|-------------------------------------|--------------------------|-----------|
|                                 |            | TWA                                 | 0.005 ppm                | CA ON OEL |
|                                 |            | C                                   | 0.02 ppm                 | CA ON OEL |
|                                 |            | TWAEV                               | 0.005 ppm<br>0.051 mg/m3 | CA QC OEL |
|                                 |            | TWA                                 | 0.005 ppm                | ACGIH     |
| Quartz (SiO <sub>2</sub> ) >5µm | 14808-60-7 | TWA (Respirable particulates)       | 0.025 mg/m3              | CA AB OEL |
|                                 |            | TWA (Respirable fraction)           | 0.1 mg/m3                | CA ON OEL |
|                                 |            | TWA (Respirable)                    | 0.025 mg/m3 (Silica)     | CA BC OEL |
|                                 |            | TWAEV (respirable dust)             | 0.05 mg/m3               | CA QC OEL |
|                                 |            | TWA (Respirable)                    | 0.025 mg/m3              | CA BC OEL |
|                                 |            | TWA (Respirable)                    | 0.025 mg/m3 (Silica)     | CA BC OEL |
|                                 |            | TWA (Respirable particulate matter) | 0.025 mg/m3              | ACGIH     |
|                                 |            | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica)     | ACGIH     |
|                                 |            | TWA (Respirable particulate matter) | 0.025 mg/m3              | ACGIH     |
|                                 |            | TWA (Respirable particulate matter) | 0.025 mg/m3 (Silica)     | ACGIH     |

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

### Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the max-



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

|                          |                                                                                                                                                                                                                                                 |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          | imum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.                                          |
| Hand protection          | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.                                                       |
| Eye protection           | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.                                                                                                                         |
| Skin and body protection | : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.                                                                                                      |
| Hygiene measures         | : Avoid contact with skin, eyes and clothing.<br>Wash hands before breaks and immediately after handling the product.<br>Remove contaminated clothing and protective equipment before entering eating areas.<br>Wash thoroughly after handling. |

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                       |                     |
|---------------------------------------|---------------------|
| Appearance                            | : paste             |
| Color                                 | : various           |
| Odor                                  | : aromatic          |
| Odor Threshold                        | : No data available |
| pH                                    | : Not applicable    |
| Melting point/ range / Freezing point | : No data available |
| Boiling point/boiling range           | : No data available |
| Flash point                           | : Not applicable    |
| Evaporation rate                      | : No data available |
| Flammability (solid, gas)             | : No data available |



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

|                                                  |   |                                            |
|--------------------------------------------------|---|--------------------------------------------|
| Upper explosion limit / Upper flammability limit | : | No data available                          |
| Lower explosion limit / Lower flammability limit | : | No data available                          |
| Vapor pressure                                   | : | 0.01 hpa                                   |
| Relative vapor density                           | : | No data available                          |
| Density                                          | : | ca. 1.51 g/cm <sup>3</sup> (23 °C (73 °F)) |
| Solubility(ies)                                  |   |                                            |
| Water solubility                                 | : | insoluble                                  |
| Solubility in other solvents                     | : | No data available                          |
| Partition coefficient: n-octanol/water           | : | No data available                          |
| Autoignition temperature                         | : | No data available                          |
| Decomposition temperature                        | : | No data available                          |
| Viscosity                                        |   |                                            |
| Viscosity, dynamic                               | : | No data available                          |
| Viscosity, kinematic                             | : | > 20.5 mm <sup>2</sup> /s                  |
| Explosive properties                             | : | No data available                          |
| Oxidizing properties                             | : | No data available                          |
| Volatile organic compounds (VOC) content         | : | 37 g/l                                     |

---

### SECTION 10. STABILITY AND REACTIVITY

|                                    |   |                                                             |
|------------------------------------|---|-------------------------------------------------------------|
| Reactivity                         | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability                 | : | The product is chemically stable.                           |
| Possibility of hazardous reactions | : | Stable under recommended storage conditions.                |
| Conditions to avoid                | : | No data available                                           |
| Incompatible materials             | : | No data available                                           |



## Sikaflex<sup>®</sup>-1A

Revision Date 03/07/2025

Print Date 03/07/2025

Hazardous decomposition : No decomposition if stored and applied as directed.  
products

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified due to lack of data.

#### Components:

##### **xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

##### **ethylbenzene:**

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

##### **4,4'-methylenediphenyl diisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50: 1.5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Expert judgment

##### **aromatic polyisocyanate:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

#### **Skin corrosion/irritation**

Not classified due to lack of data.

#### **Serious eye damage/eye irritation**

Not classified due to lack of data.

#### **Respiratory or skin sensitization**

##### **Skin sensitization**

May cause an allergic skin reaction.

##### **Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

##### **Germ cell mutagenicity**

Not classified due to lack of data.



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

### Carcinogenicity

May cause cancer by inhalation.

|             |                                                               |            |
|-------------|---------------------------------------------------------------|------------|
| <b>IARC</b> | Group 1: Carcinogenic to humans                               |            |
|             | Quartz (SiO <sub>2</sub> ) >5µm<br>(Silica dust, crystalline) | 14808-60-7 |
|             | Group 2B: Possibly carcinogenic to humans                     |            |
|             | Titanium dioxide                                              | 13463-67-7 |
|             | Group 2B: Possibly carcinogenic to humans                     |            |
| <b>OSHA</b> | Carbon black, amorphous                                       | 1333-86-4  |
|             | Group 2B: Possibly carcinogenic to humans                     |            |
|             | ethylbenzene                                                  | 100-41-4   |
| <b>OSHA</b> | OSHA specifically regulated carcinogen                        |            |
|             | Quartz (SiO <sub>2</sub> ) >5µm<br>(crystalline silica)       | 14808-60-7 |
|             |                                                               |            |
| <b>NTP</b>  | Known to be human carcinogen                                  |            |
|             | Quartz (SiO <sub>2</sub> ) >5µm                               | 14808-60-7 |
|             | (Silica, Crystalline (Respirable Size))                       |            |

### Reproductive toxicity

Not classified due to lack of data.

### STOT-single exposure

Not classified due to lack of data.

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### Aspiration toxicity

Not classified due to lack of data.

### Further information

#### Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### xylene:

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

icity) Exposure time: 56 d

Toxicity to daphnia and other : NOEC (Daphnia): 1.17 mg/l  
aquatic invertebrates (Chronic toxicity) Exposure time: 7 d

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

### TDG

Not regulated as a dangerous good

### Special precautions for user

Not applicable

---

## SECTION 15. REGULATORY INFORMATION

### Canadian lists

The following substance(s) is/are subject to a Significant New Activity Notification:  
propylene oxide 75-56-9

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

|                   |   |                                                                                                                                          |
|-------------------|---|------------------------------------------------------------------------------------------------------------------------------------------|
| ACGIH             | : | USA. ACGIH Threshold Limit Values (TLV)                                                                                                  |
| CA AB OEL         | : | Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)                                                                      |
| CA BC OEL         | : | Canada. British Columbia OEL                                                                                                             |
| CA ON OEL         | : | Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.                                         |
| CA QC OEL         | : | Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants |
| ACGIH / TWA       | : | 8-hour, time-weighted average                                                                                                            |
| CA AB OEL / TWA   | : | 8-hour Occupational exposure limit                                                                                                       |
| CA AB OEL / STEL  | : | 15-minute occupational exposure limit                                                                                                    |
| CA BC OEL / TWA   | : | 8-hour time weighted average                                                                                                             |
| CA BC OEL / STEL  | : | short-term exposure limit                                                                                                                |
| CA BC OEL / C     | : | ceiling limit                                                                                                                            |
| CA ON OEL / C     | : | Ceiling Limit (C)                                                                                                                        |
| CA ON OEL / TWA   | : | Time-Weighted Average Limit (TWA)                                                                                                        |
| CA QC OEL / TWAEV | : | Time-weighted average exposure value                                                                                                     |
| CA QC OEL / STEV  | : | Short-term exposure value                                                                                                                |
|                   |   |                                                                                                                                          |
| ADR               | : | Accord européen relatif au transport international des marchandises Dangereuses par Route                                                |
| CAS               | : | Chemical Abstracts Service                                                                                                               |
| DNEL              | : | Derived no-effect level                                                                                                                  |
| EC50              | : | Half maximal effective concentration                                                                                                     |
| GHS               | : | Globally Harmonized System                                                                                                               |
| IATA              | : | International Air Transport Association                                                                                                  |
| IMDG              | : | International Maritime Code for Dangerous Goods                                                                                          |
| LD50              | : | Median lethal dosis (the amount of a material, given all at                                                                              |



## Sikaflex®-1A

Revision Date 03/07/2025

Print Date 03/07/2025

|        |                                                                                                                                                                                                                                        |
|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        | once, which causes the death of 50% (one half) of a group of test animals)                                                                                                                                                             |
| LC50   | : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)                                                                                                 |
| MARPOL | : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978                                                                                                                        |
| OEL    | : Occupational Exposure Limit                                                                                                                                                                                                          |
| PBT    | : Persistent, bioaccumulative and toxic                                                                                                                                                                                                |
| PNEC   | : Predicted no effect concentration                                                                                                                                                                                                    |
| REACH  | : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC   | : Substances of Very High Concern                                                                                                                                                                                                      |
| vPvB   | : Very persistent and very bioaccumulative                                                                                                                                                                                             |

### Notice to Reader:

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sika.ca](http://www.sika.ca) or 514-697-2610.

|                 |                             |
|-----------------|-----------------------------|
| Revision Date   | : 03/07/2025                |
| Date format     | : mm/dd/yyyy                |
| Prepared by     | : R & D of Sika Canada Inc. |
| Material number | : 91,009                    |

CA / Z8