



BC BUILDING PRODUCTS
THE ENVELOPE SPECIALISTS

TECHNICAL DATA SHEET

Soprema SOPRAMASTIC

Manufacturer: Soprema Inc.

The following pages are the manufacturer's original document,
reproduced unaltered (revision not shown on document).

SUPPLIED BY BC BUILDING PRODUCTS

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca

Formerly known as ELASTOMERIC SEALANT by RESISTO

SOPRAMASTIC



TECHNICAL DATA SHEET 260129SCANE

(supersedes 131007SCAN7E
and 2023-06-09 by Resisto)

DESCRIPTION

SOPRAMASTIC is a black, solvent-based mastic containing SBS modified bitumen, fibres and mineral fillers. It is a complement for bituminous waterproofing membranes and is used as jointing mastic, caulking material and joint filler.

SOPRAMASTIC is a multi-purpose mastic that has been formulated with a high level of polymers in order to resist flow at high temperatures. Furthermore, it is easy to manipulate at temperatures down to -10 °C (14 °F).

RECOMMENDED SUBSTRATES

It is compatible with most construction materials, including bituminous materials.

SURFACE PREPARATION

Surfaces must be dry, clean, and free of any oil, grease, debris, or dirt.

APPLICATION

Apply SOPRAMASTIC using a standard cartridge extruder.

Application temperature: -10 to 35 °C (14 to 95 °F)

Service temperature: -40 to 80 °C (-40 to 175 °F)

RESTRICTION

- Should not be used as a pitch pocket filler.

FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

GENERAL INFORMATION

Specifications	SOPRAMASTIC
Colour	Black
Available formats	310 ml (0.08 US gal) cartridges 800 ml (0.21 US gal) cartridges 4 kg (8.8 lb) (3.6 L (0.94 US gal)) pail 10 L (2.64 US gal) pail
Coverage, per 310 ml (0.08 US gal) cartridge, for a 6 mm (1/4 in) wide bead	7.6 m (25 ft)
Setting time	4 to 24 hours ⁽¹⁾

(1): Drying times are approximate and may vary depending on temperature and the amount applied.

PROPERTIES

SOPRAMASTIC meets the requirements of CAN/CGSB-37.5-M89 and ASTM D 4586.

Properties	SOPRAMASTIC
Specific gravity, at 20 °C (68 °F)	1.12 kg/L (9.35 lb/US gal)
Solid by weight	83%



SOPREMA.CA 1 877 MAMMOUTH

NOTE : All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.
This technical data sheet applies to products sold on the Canadian market only.

Formerly known as ELASTOMERIC SEALANT by RESISTO

SOPRAMASTIC



TECHNICAL DATA SHEET **260129SCANE**

(supersedes 131007SCAN7E
and 2023-06-09 by Resisto)

CLEANING

- Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

STORAGE AND HANDLING

- SOPRAMASTIC can be kept for 36 months when properly stored in its original sealed containers.
- Store in a cool, dry and well-ventilated area. Keep away from any source of heat and humidity.
- SOPRAMASTIC is a flammable product. Keep it protected from sunlight and away from any flame. During use, no sources of ignition should be present. Do not smoke. After application, do not approach any flame until solvents have been eliminated.

FOR MORE INFORMATION, REFER TO THE INSTRUCTIONS ON THE LABEL AND RELEVANT SAFETY DATA SHEET (SDS).



SOPREMA.CA 1 877 MAMMOUTH

NOTE : All products manufactured by SOPREMA Inc. comply with the description and properties indicated in the technical data sheet that was current at the date of manufacture.
This technical data sheet applies to products sold on the Canadian market only.

sopca-en-ca-tds-sopramastic.indd