



BC BUILDING PRODUCTS
THE ENVELOPE SPECIALISTS

TECHNICAL DATA SHEET

TREMstop® Acrylic

Manufacturer: Tremco CPG Inc.

The following pages are the manufacturer's original document,
reproduced unaltered (data sheet ref. TSA-DS/0826).

SUPPLIED BY BC BUILDING PRODUCTS

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca



TECHNICAL DATA SHEET

TREMSTOP® ACRYLIC

Gunnable, Acrylic Latex Firestop
Sealant

PRODUCT DESCRIPTION

TREMstop® Acrylic is a gunnable, acrylic latex sealant designed for use in firestopping applications, including both joints and through-penetrations. TREMstop Acrylic can also be used in smoke-rated partitions or joints and to prevent sound transmission through unprotected openings.

BASIC USES

TREMstop Acrylic is intended for use in fire-rated concrete, wood, floor/ceiling, and gypsum assemblies, including the following:

- Metal or insulated pipes
- Ducts
- Static joints
- Dynamic joints
- Acoustically rated assemblies

Additionally, TREMstop Acrylic can be used for through penetrations and joints in smoke- and/or sound-rated partitions and to restore the STC of sound-rated assemblies.

FEATURES & BENEFITS

TREMstop Acrylic is an easy to apply, multipurpose sealant that accepts paint once fully cured. It features excellent movement and superb unprimed adhesion to a wide range of substrates. When installed in accordance with a tested firestop system, TREMstop Acrylic affords code compliance for both through-penetrations and fire-rated joints. It also provides a fast and easy solution for restoring the STC rating of a sound-rated assembly.

TREMstop Acrylic meets or exceeds the requirements of the following specifications:

- UL 1479 (ASTM E814)
- UL 263 (ASTM E119)
- UL 723 (ASTM E84)
- UL 2079 (ASTM E1966)
- ASTM E1399
- ASTM E90
- CAN/ULC-S115
- CAN/ULC-S101M

The Greenguard Gold certification on TREMstop Acrylic ensures safety for use in the most sensitive indoor environments including hospitals and schools.

AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 10.1 oz (300 mL) cartridges, 20 oz (600 mL) sausages, 28.7 oz (850 mL) quart cartridges, and 5 gal (19 L) pails.

COLORS

Available in Rust Red, Limestone, and White.

All colors are not available in all package sizes. Some colors may require a minimum quantity. Contact Tremco Customer Service for more information.

LIMITATIONS

Not recommended for use with passive fire containment systems not listed or approved by Tremco. Refer to UL listings at www.UL.com. Contact Tremco Technical Services for additional information.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES		
PROPERTY	TEST METHOD	TYPICAL RESULTS
Flame Spread	ASTM E84	20
Smoke Development	ASTM E84	55
Movement Capability	ASTM C719, UL2079; Class I, II, III	± 33%
STC Rating	ASTM E90	67
OITC Rating	ASTM E90	55
Peel Strength	ASTM C794	15 to 25 (substrate dependent)
VOC Content		35 g/L



Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TSA-DS/0826

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com