



BC BUILDING PRODUCTS
THE ENVELOPE SPECIALISTS

TECHNICAL DATA SHEET

TREMstop® MP

Manufacturer: Tremco CPG Inc.

The following pages are the manufacturer's original document,
reproduced unaltered (data sheet ref. 0316/TSMPDS-ST).

SUPPLIED BY BC BUILDING PRODUCTS

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca

Product Description

TREMstop® MP is a moldable putty preshaped into three pad sizes to fit different electrical boxes. Release liners are on both sides of the pad and one must be removed for installation.

Basic Uses

TREMstop MP is for use with metal and plastic electrical outlet boxes in gypsum wall assemblies.

Features and Benefits

- TREMstop MP is pliable and has excellent adhesive strength making installation by hand fast and easy. One side of the release liner can be left in place keeping hands clean during installation. The thickness of the pad prevents tearing on the corners of metal outlet boxes.

Availability

Immediately available from your local Tremco Field Representative, Tremco Distributor or Tremco Warehouse.

Packaging

6" x 7" x .2" (152 mm x 178 mm x 5 mm) 12 pads/case

7.25" x 7.25" x .2" (184 mm x 184 mm x 5 mm) 12 pads/case

9.25" x 9.25" x .2" (235 mm x 235 mm x 5 mm) 12 pads/case

Colors

Rust Red

Applicable Standards

- UL 263
- CAN/ULC-S101

Limitations

- Not recommended for use with passive fire containment systems not listed or approved by Tremco.

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase price of the quantity of Tremco Products proven to be defective and Tremco shall not be liable for any loss or damage.


Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Flame Spread	ASTM E84	Restored to 61 in a U411 wall
STC	ASTM E90	Restored to 61 in a U411 wall

0316/TSMPS-ST



Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555