



BC BUILDING PRODUCTS
THE ENVELOPE SPECIALISTS

TECHNICAL DATA SHEET

TREMstop® Smoke & Sound SP

Manufacturer: Tremco CPG Inc.

The following pages are the manufacturer's original document,
reproduced unaltered (data sheet ref. 0316/TSSSSPDS-ST).

SUPPLIED BY BC BUILDING PRODUCTS

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca

TREMstop® Smoke & Sound Spray

A Sprayable Acrylic Latex Sealant

Product Description

TREMstop® Smoke & Sound Spray is an acrylic latex sealant for use in smoke rated partitions or joints and to prevent sound transmission through unprotected openings.

Basic Uses

TREMstop Smoke & Sound Spray may be used for both through-penetrations and joints in smoke or sound rated partitions.

Features and Benefits

- TREMstop Smoke & Sound Spray is designed to meet the needs of both smoke and sound rated partitions with one product. It can be painted once dry and is easily cleaned up with soapy water. The spray application affords labor savings, especially on long joint runs.

Availability

Immediately available from your local Tremco Field Representative, Tremco Distributor or Tremco Warehouse.

Coverage Rates

12.83 ft²/gal

Packaging

5-gal (19-L) pails

Colors

White

Shelf Life

Minimum 1 year when stored at 40 to 110 °F (5 to 43 °C)

Limitations

- Not for use in fire-rated assemblies.

Clean Up

Excess sealant can be cleaned up or removed with soapy water before sealant skins. Clean sprayer in accordance with manufacturer's recommended cleaning instructions.

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase price of the quantity of Tremco Products proven to be defective and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
V.O.C. Content		35 g/L
Movement Capability	ASTM C719	+/- 25%
STC	ASTM E90	Restored to 59 in a U411 wall
Peel Strength	ASTM C794	8 to 14 (substrate dependent)
pH		7 to 9
Antifungal		Contains antifungal additive

0316/TSSSPDS-ST

Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555

