



BC BUILDING PRODUCTS
THE ENVELOPE SPECIALISTS

TECHNICAL DATA SHEET

Tremco Acoustical/ Curtainwall Sealant

Manufacturer: Tremco CPG Inc.

The following pages are the manufacturer's original document,
reproduced unaltered (data sheet ref. ACSTCL-DS/0723).

SUPPLIED BY BC BUILDING PRODUCTS

8241 129 St, Surrey, BC V3W 0A6

604-540-9040 · sales@bcbp.ca · bcbp.ca



TECHNICAL DATA SHEET

ACOUSTICAL/ CURTAINWALL SEALANT

One-Part, Non-Skinning, Sound
Dampening Sealant

PRODUCT DESCRIPTION

Tremco® Acoustical/Curtainwall Sealant is a single-component, non-skinning, non-hardening synthetic rubber sealant intended for use in sound dampening systems.

BASIC USES

Tremco Acoustical/Curtainwall Sealant was developed for acoustical sealing of the following:

- Drywall partitions
- Curtainwalls
- Corridors
- Party walls

FEATURES & BENEFITS

The application of Tremco Acoustical/Curtainwall Sealant greatly increases the Sound Transmission Class (STC value) of a system and reduces the decibel level when one or more beads are applied to a joint.

Tremco Acoustical/Curtainwall Sealant does not cure or dry by design. It is a non-skinning, non-hardening formula that will remain viscous and tacky to further aid in decreasing sound transmission.

AVAILABILITY

Immediately available from your local Tremco Sales Representative, Tremco Distributor, or Tremco Warehouse in 10.1 oz (300 mL) cartridges, 1 qt (850 mL) cartridges, and 5 gal (19 L) pails.

COLORS

Available in Dark Gray.

LIMITATIONS

Do not apply to damp or contaminated surfaces. Use with adequate ventilation.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL RESULTS
Resistance to Sag	CGSB 7.1	Passes
Extrusion Rate	CGSB 3.1	Passes
Viscosity	CGSB Brookfield	1,000,000 cps
Loss of Mass	CGSB 5.1	Passes
Resistance to Staining & Bleeding	CGSB 9.2	Passes
Low Temperature Flexibility	CGSB 11.1	Passes, -10 °C
Cracking/Blistering	CGSB 19.2	Passes
Shear Modulus	Using GR component	45,000 N/m ²
Density		1,720 kb/m ³

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

ACSTCL-DS/0723

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com